


DGPH M 255 (961 102)


- Discharge capacity up to 100 kA (10/350 μ s)
- Total current arrester specifically designed for installation in "3+1" and "1+1" circuits of TT systems according to IEC 60364-5-53 between neutral conductor N and protective conductor PE
- Creepage discharge spark gap technology



Figure without obligation



Basic circuit diagram DGPH M 255



Dimension drawing DGPH M 255

Modular single-pole N-PE lightning current arrester for $U_c = 255$ V.

Type Part No.	DGPH M 255 961 102
SPD according to EN 61643-11 / IEC 61643-11	type 1 / class I
Max. continuous operating voltage (a.c.) (U_c)	255 V (50 / 60 Hz)
Lightning impulse current (10/350 μ s) (I_{imp})	100 kA
Specific energy (W/R)	2.50 MJ/ohms
Voltage protection level (U_P)	≤ 4 kV
Follow current extinguishing capability (a.c.) (I_n)	100 A _{rms}
Response time (t_A)	≤ 100 ns
Temporary overvoltage (TOV) (U_T) – Characteristic	1200 V / 200 ms – withstand
Operating temperature range (parallel connection) (T_{UP})	-40 °C ... +80 °C
Operating temperature range (series connection) (T_{US})	-40 °C ... +60 °C
Number of ports	1
Cross-sectional area (min.)	10 mm ² solid / flexible
Cross-sectional area (max.)	50 mm ² stranded / 35 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	2 module(s), DIN 43880
Weight	284 g
Customs tariff number (Comb. Nomenclature EU)	85363030
GTIN	4013364118690
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.